

MYTHO 8

ACTIVE TWO-WAY 8" DSP MONITORING SYSTEM



FEATURES

- True active 200 W + 100 W class AB design
 - Dedicated DSP processing
 - Fully featured input board
 - 8" neodymium ICC vented woofer
 - 1" aluminum dome tweeter
 - Constant directivity wave-guide
 - Die cast aluminum cabinet
 - Reflection free cabinet design
 - Low distortion reflex port
-

TECHNICAL SPECIFICATIONS

Acoustical specifications	Max SPL @ 1m:	116 dB
	Horizontal coverage angle:	110°
	Vertical coverage angle:	70°
<hr/>		
Input/Output section	Input signal:	bal/unbal
	Input connectors:	Combo XLR/Jack
	Input sensitivity:	-6 dBu/+6 dBu
<hr/>		
Processor section	Protections:	Thermal, Excurs., RMS
	Limiter:	Soft Limiter
	Controls:	Bass tilt, roll-off, treble tilt, desktop, DSP Controlled
<hr/>		
Power section	Total Power:	600 W Peak, 300 W RMS
	High frequencies:	200 W Peak, 100 W RMS
	Low frequencies:	400 W Peak, 200 W RMS
	Cooling:	Convection
	Connections:	VDE
<hr/>		
Standard compliance	CE marking:	Yes
<hr/>		
Physical specifications	Cabinet/Case Material:	Aluminium
	Hardware:	Orientation adjustable stand
	Color:	Black
<hr/>		
Size	Height:	430 mm / 16.93 inches
	Width:	310 mm / 12.2 inches
	Depth:	300 mm / 11.81 inches
	Weight:	16.15 kg / 35.6 lbs
<hr/>		
Shipping informations	Package Height:	529 mm / 20.83 inches
	Package Width:	414 mm / 16.3 inches
	Package Depth:	414 mm / 16.3 inches
	Package Weight:	17.77 kg / 39.18 lbs

PART NUMBER• **13000195**

MYTHO 8

220-240V, Black

EAN 8024530008659